

ISGUS Terminal IT 450



- Terminals for access control with swipe reader or proximity reader.
- Door opening via integrated relay or external door control (TSE 400, Device I/O).
- High security via connection a intelligent access controller ACM 200 / 400 / 4001.
- Status display and booking acknowledgement via LED and acoustic signal.
- Anti-tamper alarm device.
- Door opening function also in offline mode.
- Simple and flexible installation.
- Numeric keypad for PIN entry.
- Proximity reader also suitable for outdoor environments.





Technical Data IT 450

Badge reader systems:	ISGUS proximity, Hitag 1, Legic, Mifare, SimonsVoss, Infra-red reader, Chipcard insert reader, Magnetic stripe reader DIN 9785, ISO 7810/11, EN 27810/11 track 2, LoCo, HiCO
Voltage:	8 - 12 V AC or 12 - 16 V DC
Current consumption:	0,2 A - 0,5 A depending on reader type
Protection type: Protection class:	IP 42 (IP 55 for proximity reader) II / EN 60950
Environment:	Ambient temperature: -10° to + 70° C No direct sunlight
Rel. humidity:	max. 85 % (non condensing)
Data communication:	RS 485, 2-wire
Weight:	Approx. 0,7 kg
Dimensions:	Height: 86 mm Width: 193 mm Depth: 82 mm

subject to technical modifications

