

ISGUS Terminal IT 8260



Multifunctional Touchscreen-Terminal for:

- » Time & Attendance
- » Employee-self-service
- » Cost Center Change
- » Plant Data Collection
- » Job costing

in rough manufacturing environments



IT 8260 for Time & Attendance and Employee-self-service

- » Touch screen with large key- and function symbols for convenient and easy handling
- » For time bookings such as IN, OUT, cost centre change, etc.
- » Time bookings via IN/OUT keys or automatic booking allocation
- » Easy generation of workflow requests via touch screen for absences such as holidays, business trips, vocational training, etc.
- » Easy generation of workflow requests for totals updating, forgotten bookings, shift changes, etc.
- » Precise inquiry of time accounts such as balance, overtime, remaining holidays
- » Non limited number of absence reasons such as official absence, business trip, medical appointment, etc.
- » Saving of an arbitrary number of bookings




IT 8260 for Plant Data Collection (optional)

- » Multi company operation (max. 50 companies)
- » Integration into existing IT structures via DHCP and DNS
- » Easy and quick recording of PDC bookings such as order start, change or end
- » Comfortable and fast selection of order and PDC bookings such as order start, order change or end, good yield or reject quantities, etc.
- » USB port for data collection via barcode scanner
- » Robust housing with easy to clean glass front
- » Protected touchscreen through glass panel (3 mm)

Technical Information Terminal

IT 8260



Badge reader systems

- » ISGUS-Prox
- » hitag 1
- » LEGIC
- » LEGIC advant
- » Mifare
- » Mifare DESFire
- » Em4102
- » others upon request

Touchscreen

- » 15" TFT colour display with capacitive touch function
- » Resolution: 1024 x 768
- » Touch surface, glass: 3 mm, two point projected capacitive technology

Voltage

- » Internal power supply unit: 230 V AC

Power consumption

- » 16,1 W

Protection type

- » IP 65

Protection class

- » I / En62368-1

Rel. humidity

- » max. 85 %

Ambient temperature

- » -5°C to +40 °C

Network connection

- » Ethernet 10/100/1000 MBit
- » RJ-45

Weight

- » Approx. 4,5 kg

Dimensions

- » Height: 334 mm
- » Width: 360 mm
- » Depth: 90 mm



ISGUS GmbH
Oberdorfstr. 18-22
78054 Villingen-Schwenningen

Tel. +49 7720 393-0
Fax +49 7720 393-184

info@isgus.de
www.isgus.de